

1. What is incoherence?


In an MDP with a prior over actions $p(a|s)$ and a binary reward R , the goal-conditioned policy $\pi(a|s) = p(a|s, R = 1)$ answers the question:

? Which action to take in state s , such that, if later choices are sampled from the **prior** $p(a|s)$ the outcome will lead to R ?

rather than

? Which action to take in state s , such that, if later choices are sampled from the policy $\pi(a|s)$ the outcome will lead to R ?

2. Example: mountain race



The goal-conditioned policy is computed as:

$$\pi(a|\emptyset) = p(a|\emptyset, R = 1) = \frac{p(R = 1|\emptyset, a) p(a|\emptyset)}{p(R = 1|\emptyset)} \propto p(R = 1|\emptyset, a)$$

evaluating later actions according to the prior:

$$\pi(\nearrow|\emptyset) \propto p(R = 1|\emptyset, \nearrow) = p(R = 1|\text{peak}) = \frac{1}{2}$$

$$\pi(\searrow|\emptyset) \propto p(R = 1|\emptyset, \searrow) = p(R = 1|\text{tree}) = \frac{3}{4}$$

even though the goal-conditioned policy would avoid the chasm!

3. Formalising incoherence

Incoherence is the gap between π and the policy recommended by π 's own future Q-values:


$$\text{Incoherence}_\tau(\pi) = \text{KL}_\xi [\pi(\xi) \parallel \text{Boltzmann}_\tau(Q^\pi)(\xi)]$$

over trajectories $\xi = (s_0, a_0, \dots, s_n)$

$$\text{where } \text{Boltzmann}_\tau(Q^\pi)(a|s) \propto \exp\left(\frac{Q^\pi(a, s)}{\tau}\right)$$

4. Three-way correspondence

Three equivalent views of policy tightening:



Theorem (Optimisation pressure, thrice). For all priors $p(a|s)$, all non-positive reward functions $r(s_t, a_t)$ and deterministic transition dynamics $\tau(s_{t+1}|s_t, a_t)$, for all $k \in \mathbb{N}_+$ and for $\alpha(k) = 2^k$, we have:


$$\pi_{\alpha(k)} = \pi_{2^k}^{\mathcal{G}} = \pi_{2^k}^{\mathcal{F}} = \pi_k^{\mathcal{H}}$$

Additionally, for stochastic transition dynamics we have:


$$\pi_k^{\mathcal{F}} = \pi_k^{\mathcal{G}}$$

5. Effective horizon

When actions with the highest Q-values under the random policy also have the highest Q-values under the optimal policy (i.e. when it is optimal to be greedy on the random policy's Q-function), deep RL tends to succeed; when they don't, deep RL tends to fail. (Laidlaw et al., 2023)





Monte Carlo effective horizon estimation:



6. Incoherence as a metric

A corollary of the theorem:

$$\lim_{(\tau, i) \rightarrow (0, \infty)} \text{Incoherence}_\tau(\pi_i^{\mathcal{G}}) = 0$$



The average correlation between return and negative incoherence across a dataset of trajectories: 0.863

